



Mi CB 10



- Connection Box

ELECTRICAL PROPERTIES

Protection class: II

CONNECTION DATA

MECHANICAL PROPERTIES

Delivered accessories: Fastening material
IP degree of protection: IP65
Suitable for box wall: 300 mm

AMBIENT CONDITIONS

Application area: Indoor installation
Maximum ambient temperature 24 h: 35 °C
Ambient temperature: -5 °C up to +40 °C
Relative humidity: ≤ 50 % at 40 °C, ≤ 100 % at 25 °C

MATERIAL PROPERTIES

Material: Polycarbonate

DIMENSIONS

Height:	150 mm
Width:	300 mm
Depth:	170 mm
Net weight:	0.966 kg
Mounting height:	125 mm
Mounting width:	240 mm

COLOURS

Colour: Grey, similar to RAL 7035

CERTIFICATES

conforming to the standards: IEC 61439-2

SALES DATA

Product number:	20001071
EAN:	4012591111610
Pack unit:	1
Customs tariff number:	85371098
ETIM class:	DYNAMIC: EC000784 - Desk system (enclosure/cabinet) ETIM-9.0: EC000784 - Desk system (enclosure/cabinet) ETIM-8.0: EC000784 - Desk system (enclosure/cabinet) ETIM-7.0: EC000784 - Desk system (enclosure/cabinet) ETIM-6.0: EC000784 - Desk system (enclosure/cabinet) ETIM-5.0: EC000784 - Desk system (enclosure/cabinet) ETIM-4.0: EC000784 - Desk system (enclosure/cabinet)

NOTE

Note on the product:

- For sub-construction
- For the installation of devices that have to be operated from the outside.

TENDER TEXT

Insulation-enclosed power distribution board as power switchgear and controlgear assembly (PSC) in accordance with IEC 61439-2 for wall mounting. The enclosures must be suitable for outdoor installation - harsh environment and/or outdoor installation - the climatic effects on the equipment must be considered.

Bottom parts and lids of the boxes made from impact-resistant polycarbonate, halogen and silicone-free, colour RAL 7035, transparent lid with quick action fasteners for tool operation. Burning behaviour according to IEC 60695-2-11 glow wire test + 960°C. Maximum water absorption 10 mg in accordance with DIN 53473. Protective measure: totally insulated (protection class II), Make: HENSEL Mi Power distribution board., Mi Connection Box for the installation of devices that must be operated externally, such as plugs, pushbuttons and switches. Degree of protection: IP 65 in accordance with IEC 60 529. Dimensions HxWxD 150 x 300 x 170 mm

DRAWINGS

