



Mi EP 02

- Cover
- twigTest

CONNECTION DATA

MECHANICAL PROPERTIES

Delivered accessories:
Suitable for box size:

Fastening material
2

AMBIENT CONDITIONS

Application area:
Maximum ambient temperature 24 h:
Ambient temperature:
Relative humidity:

Indoor installation
35 °C
-5 °C up to +40 °C
≤ 50 % at 40 °C, ≤ 100 % at 25 °C

MATERIAL PROPERTIES

Material:
Polycarbonate

DIMENSIONS

Height:	286 mm
Width:	286 mm
Net weight:	0.34 kg

CERTIFICATES

conforming to the standards: IEC 61439-2

SALES DATA

Product number:	2000695
EAN:	4012591656951
Pack unit:	1
Customs tariff number:	85371098
ETIM class:	DYNAMIC: EC000201 - Built-in panel for command devices ETIM-9.0: EC000201 - Built-in panel for command devices ETIM-8.0: EC000201 - Built-in panel for command devices ETIM-7.0: EC000201 - Built-in panel for command devices ETIM-6.0: EC000201 - Built-in panel for command devices ETIM-5.0: EC000201 - Built-in panel for command devices ETIM-4.0: EC000201 - Built-in panel for command devices

TENDER TEXT

Insulation-enclosed power distribution board as power switchgear and controlgear assembly (PSC) in accordance with IEC 61439-2 for wall mounting. The enclosures must be suitable for outdoor installation - harsh environment and/or outdoor installation - the climatic effects on the equipment must be considered. Bottom parts and lids of the boxes made from impact-resistant polycarbonate, halogen and silicone-free, colour RAL 7035, transparent lid with quick action fasteners for tool operation. Burning behaviour according to IEC 60695-2-11 glow wire test + 960°C. Maximum water absorption 10 mg in accordance with DIN 53473. Protective measure: totally insulated (protection class II), Make: HENSEL Mi Power distribution board., Cover plate Mi EP 02 for Mi 02..

DRAWINGS



