



## Mi EP 04

- Cover
- twigTest

### CONNECTION DATA

### MECHANICAL PROPERTIES

Delivered accessories:  
Suitable for box size:

Fastening material  
4

### AMBIENT CONDITIONS

Application area:  
Maximum ambient temperature 24 h:  
Ambient temperature:  
Relative humidity:

Indoor installation  
35 °C  
-5 °C up to +40 °C  
≤ 50 % at 40 °C, ≤ 100 % at 25 °C

## MATERIAL PROPERTIES

Material: Polycarbonate

## DIMENSIONS

Height: 586 mm  
Width: 286 mm  
Net weight: 0.58 kg

## CERTIFICATES

conforming to the standards: IEC 61439-2

## SALES DATA

Product number: 2000696  
EAN: 4012591656968  
Pack unit: 1  
Customs tariff number: 85371098  
ETIM class: DYNAMIC: EC000201 - Built-in panel for command devices  
ETIM-9.0: EC000201 - Built-in panel for command devices  
ETIM-8.0: EC000201 - Built-in panel for command devices  
ETIM-7.0: EC000201 - Built-in panel for command devices  
ETIM-6.0: EC000201 - Built-in panel for command devices  
ETIM-5.0: EC000201 - Built-in panel for command devices  
ETIM-4.0: EC000201 - Built-in panel for command devices

## TENDER TEXT

Insulation-enclosed power distribution board as power switchgear and controlgear assembly (PSC) in accordance with IEC 61439-2 for wall mounting. The enclosures must be suitable for outdoor installation - harsh environment and/or outdoor installation - the climatic effects on the equipment must be considered. Bottom parts and lids of the boxes made from impact-resistant polycarbonate, halogen and silicone-free, colour RAL 7035, transparent lid with quick action fasteners for tool operation. Burning behaviour according to IEC 60695-2-11 glow wire test + 960°C. Maximum water absorption 10 mg in accordance with DIN 53473. Protective measure: totally insulated (protection class II), Make: HENSEL Mi Power distribution board., Cover plate Mi EP 04 for Mi 04..

## DRAWINGS

