



Mi FP 30



- Metal insert

CONNECTION DATA

MECHANICAL PROPERTIES

Delivered accessories:
IP degree of protection:
Suitable for box wall:

Fastening material
IP65
300 mm

AMBIENT CONDITIONS

Application area:
Maximum ambient temperature 24 h:
Ambient temperature:
Relative humidity:

Indoor installation
35 °C
-5 °C up to +40 °C
≤ 50 % at 40 °C, ≤ 100 % at 25 °C

MATERIAL PROPERTIES

Material:

Galvanised sheet steel

DIMENSIONS

Width: 300 mm
Depth: 100 mm
Net weight: 0.294 kg
Mounting height: 88 mm
Mounting width: 215 mm

CERTIFICATES

conforming to the standards:

IEC 61439-2

SALES DATA

Product number:	20001126
EAN:	4012591102847
Pack unit:	1
Customs tariff number:	85371098
ETIM class:	DYNAMIC: EC000211 - Gland plate for enclosure/cabinet ETIM-9.0: EC000211 - Gland plate for enclosure/cabinet ETIM-8.0: EC000211 - Gland plate for enclosure/cabinet ETIM-7.0: EC000211 - Gland plate for enclosure/cabinet ETIM-6.0: EC000211 - Gland plate for enclosure/cabinet ETIM-5.0: EC000211 - Gland plate for enclosure/cabinet ETIM-4.0: EC000211 - Gland plate for enclosure/cabinet

NOTE

Note on the product:

- for earthing of metal armoured cables

TENDER TEXT

Insulation-enclosed power distribution board as power switchgear and controlgear assembly (PSC) in accordance with IEC 61439-2 for wall mounting. The enclosures must be suitable for outdoor installation - harsh environment and/or outdoor installation - the climatic effects on the equipment must be considered. Bottom parts and lids of the boxes made from impact-resistant polycarbonate, halogen and silicone-free, colour RAL 7035, transparent lid with quick action fasteners for tool operation. Burning behaviour according to IEC 60695-2-11 glow wire test + 960°C. Maximum water absorption 10 mg in accordance with DIN 53473. Protective measure: totally insulated (protection class II), Make: HENSEL Mi Power distribution board., Flange Mi FP 30 without knockouts, for flange Mi FP 20, box wall 300 mm