



Mi FP 82

IP
54

- Flange

CONNECTION DATA

CABLE ENTRIES

Cable entries:

Number of cable entries	Type of cable entry	Sealing range of the cable entry	Location of cable entry
2	Insert	30 mm - 72 mm	wall

MECHANICAL PROPERTIES

Delivered accessories:
IP degree of protection:
Suitable for box wall:

Fastening material
IP54
300 mm

AMBIENT CONDITIONS

Application area:
Maximum ambient temperature 24 h:
Ambient temperature:
Relative humidity:

Indoor installation
35 °C
-5 °C up to +40 °C
≤ 50 % at 40 °C, ≤ 100 % at 25 °C

DIMENSIONS

Height:	135 mm
Width:	300 mm
Depth:	100 mm
Net weight:	0.976 kg

CERTIFICATES

conforming to the standards: IEC 61439-2

SALES DATA

Product number:	2000319
EAN:	4012591653196
Pack unit:	1
Customs tariff number:	85371098
ETIM class:	DYNAMIC: EC000211 - Gland plate for enclosure/cabinet ETIM-9.0: EC000211 - Gland plate for enclosure/cabinet ETIM-8.0: EC000211 - Gland plate for enclosure/cabinet ETIM-7.0: EC000211 - Gland plate for enclosure/cabinet ETIM-6.0: EC000211 - Gland plate for enclosure/cabinet ETIM-5.0: EC000211 - Gland plate for enclosure/cabinet ETIM-4.0: EC000211 - Gland plate for enclosure/cabinet

NOTE

Note on the product:

- Degree of protection IP 54 only with additional strain and pressure relief

TENDER TEXT

Insulation-enclosed power distribution board as power switchgear and controlgear assembly (PSC) in accordance with IEC 61439-2 for wall mounting. The enclosures must be suitable for outdoor installation - harsh environment and/or outdoor installation - the climatic effects on the equipment must be considered. Bottom parts and lids of the boxes made from impact-resistant polycarbonate, halogen and silicone-free, colour RAL 7035, transparent lid with quick action fasteners for tool operation. Burning behaviour according to IEC 60695-2-11 glow wire test + 960°C. Maximum water absorption 10 mg in accordance with DIN 53473. Protective measure: totally insulated (protection class II), Make: HENSEL Mi Power distribution board., Flange Mi FP 82, 2 x Ø 30 to 72, as cable insert, IP 54, with stepped glands, for box wall 300 mm

DRAWINGS

