



Mi KL 12

IP
65

- Hinged flap
- Opening dimension: 60 x 220 mm

CONNECTION DATA

MECHANICAL PROPERTIES

Delivered accessories:	Fastening material
IP degree of protection:	IP65
With hinged flap:	Yes

AMBIENT CONDITIONS

Application area:	Indoor installation
Maximum ambient temperature 24 h:	35 °C
Ambient temperature:	-5 °C up to +40 °C
Relative humidity:	≤ 50 % at 40 °C, ≤ 100 % at 25 °C

DIMENSIONS

Height:	112 mm
Width:	249 mm
Depth:	15 mm
Net weight:	0.145 kg

CERTIFICATES

conforming to the standards: IEC 61439-2

SALES DATA

Product number:	2000059
EAN:	4012591650591
Pack unit:	1
Customs tariff number:	85371098
ETIM class:	DYNAMIC: EC002527 - Window (enclosure/cabinet) ETIM-4.0: EC002527 - Window (enclosure/cabinet) ETIM-5.0: EC002527 - Window (enclosure/cabinet) ETIM-6.0: EC002527 - Window (enclosure/cabinet) ETIM-7.0: EC002527 - Window (enclosure/cabinet)

NOTE

Note on the product:

- Hinged flap lockable with accessories

TENDER TEXT

Insulation-enclosed power distribution board as power switchgear and controlgear assembly (PSC) in accordance with IEC 61439-2 for wall mounting. The enclosures must be suitable for outdoor installation - harsh environment and/or outdoor installation - the climatic effects on the equipment must be considered. Bottom parts and lids of the boxes made from impact-resistant polycarbonate, halogen and silicone-free, colour RAL 7035, transparent lid with quick action fasteners for tool operation. Burning behaviour according to IEC 60695-2-11 glow wire test + 960°C. Maximum water absorption 10 mg in accordance with DIN 53473. Protective measure: totally insulated (protection class II), Make: HENSEL Mi Power distribution board., Hinged flap Mi KL 12, for 12 modules

DRAWINGS

