



Mi KL 6

IP
65

- Hinged flap
- Opening dimension: 60 x 117 mm

CONNECTION DATA

MECHANICAL PROPERTIES

| | |
|--------------------------|--------------------|
| Delivered accessories: | Fastening material |
| IP degree of protection: | IP65 |
| With hinged flap: | Yes |

AMBIENT CONDITIONS

| | |
|-----------------------------------|-----------------------------------|
| Application area: | Indoor installation |
| Maximum ambient temperature 24 h: | 35 °C |
| Ambient temperature: | -5 °C up to +40 °C |
| Relative humidity: | ≤ 50 % at 40 °C, ≤ 100 % at 25 °C |

DIMENSIONS

| | |
|-------------|---------|
| Height: | 112 mm |
| Width: | 141 mm |
| Depth: | 15 mm |
| Net weight: | 0.12 kg |

CERTIFICATES

conforming to the standards:

IEC 61439-2

SALES DATA

Product number: 2000060
EAN: 4012591650607
Pack unit: 1
Customs tariff number: 85371098
ETIM class: DYNAMIC: EC002527 - Window (enclosure/cabinet)
ETIM-4.0: EC002527 - Window (enclosure/cabinet)
ETIM-5.0: EC002527 - Window (enclosure/cabinet)
ETIM-6.0: EC002527 - Window (enclosure/cabinet)
ETIM-7.0: EC002527 - Window (enclosure/cabinet)

NOTE

Note on the product:

- Hinged flap lockable with accessories

TENDER TEXT

Insulation-enclosed power distribution board as power switchgear and controlgear assembly (PSC) in accordance with IEC 61439-2 for wall mounting. The enclosures must be suitable for outdoor installation - harsh environment and/or outdoor installation - the climatic effects on the equipment must be considered. Bottom parts and lids of the boxes made from impact-resistant polycarbonate, halogen and silicone-free, colour RAL 7035, transparent lid with quick action fasteners for tool operation. Burning behaviour according to IEC 60695-2-11 glow wire test + 960°C. Maximum water absorption 10 mg in accordance with DIN 53473. Protective measure: totally insulated (protection class II), Make: HENSEL Mi Power distribution board., Hinged flap Mi KL 6, for 6 modules

DRAWINGS

