



Mi MS 2

- Mounting profile

CONNECTION DATA

MECHANICAL PROPERTIES

Delivered accessories:

Fastening material

AMBIENT CONDITIONS

Application area:

Indoor installation

Maximum ambient temperature 24 h:

35 °C

Ambient temperature:

-5 °C up to +40 °C

Relative humidity:

≤ 50 % at 40 °C, ≤ 100 % at 25 °C

MATERIAL PROPERTIES

Material:

Sheet steel

Surface treatment:

Powder-coated, sendzimir galvanised

DIMENSIONS

Height:

1950 mm

Width:

43 mm

Depth:

62 mm

Net weight:

3.539 kg

COLOURS

Colour:

Anthracite, similar to RAL 7016

CERTIFICATES

conforming to the standards:

IEC 61439-2

SALES DATA

Product number: 2000415
EAN: 4012591654155
Pack unit: 1
Customs tariff number: 85371098
ETIM class: DYNAMIC: EC002622 - Components for arrangement/baying system (enclosure/cabinet)
ETIM-9.0: EC002622 - Components for arrangement/baying system (enclosure/cabinet)
ETIM-8.0: EC002622 - Components for arrangement/baying system (enclosure/cabinet)
ETIM-7.0: EC002622 - Components for arrangement/baying system (enclosure/cabinet)
ETIM-6.0: EC002622 - Components for arrangement/baying system (enclosure/cabinet)
ETIM-5.0: EC002622 - Components for arrangement/baying system (enclosure/cabinet)
ETIM-4.0: EC002622 - Components for arrangement/baying system (enclosure/cabinet)

NOTE

Note on the product:

- for Mi distribution board assemblies up to 900 x 1200 mm

TENDER TEXT

Mi MS 2 mounting profile for wall mounting Mi distribution boards up to 900 x 1200 mm, sendzimir galvanised and powder-coated, colour RAL 7016, length 1950 mm, with screws

DRAWINGS

