



Mi SN 4



- Locking device insertion conversion kit
- Set with 4 pieces
- Hand closure

CONNECTION DATA

MECHANICAL PROPERTIES

Type of lid fastening: Hand closure

AMBIENT CONDITIONS

Application area:	Indoor installation
Maximum ambient temperature 24 h:	35 °C
Ambient temperature:	-5 °C up to +40 °C
Relative humidity:	≤ 50 % at 40 °C, ≤ 100 % at 25 °C

DIMENSIONS

Net weight: 0.015 kg

CERTIFICATES

conforming to the standards: IEC 61439-2

SALES DATA

Product number: 2000014
EAN: 4012591650140
Pack unit: 1
Customs tariff number: 85371098
ETIM class: DYNAMIC: EC002620 - Components for installation (enclosure/cabinet)
ETIM-4.0: EC002620 - Components for installation (enclosure/cabinet)
ETIM-5.0: EC002620 - Components for installation (enclosure/cabinet)
ETIM-6.0: EC002620 - Components for installation (enclosure/cabinet)
ETIM-7.0: EC002620 - Components for installation (enclosure/cabinet)

NOTE

Note on the product:

- Conversion kit from tool actuation to manual operation

TENDER TEXT

Insulation-enclosed power distribution board as power switchgear and controlgear assembly (PSC) in accordance with IEC 61439-2 for wall mounting. The enclosures must be suitable for outdoor installation - harsh environment and/or outdoor installation - the climatic effects on the equipment must be considered. Bottom parts and lids of the boxes made from impact-resistant polycarbonate, halogen and silicone-free, colour RAL 7035, transparent lid with quick action fasteners for tool operation. Burning behaviour according to IEC 60695-2-11 glow wire test + 960°C. Maximum water absorption 10 mg in accordance with DIN 53473. Protective measure: totally insulated (protection class II), Make: HENSEL Mi Power distribution board., Conversion kit Mi SN 4, for converting lid fastener to manual operation, 4 pieces