



Mi WD 2

- Wall gasket

CONNECTION DATA

MECHANICAL PROPERTIES

Delivered accessories:
Suitable for box wall:

Fastening material
150 mm, 300 mm

AMBIENT CONDITIONS

Application area:
Maximum ambient temperature 24 h:
Ambient temperature:
Relative humidity:

Indoor installation
35 °C
-5 °C up to +40 °C
≤ 50 % at 40 °C, ≤ 100 % at 25 °C

DIMENSIONS

Net weight:

0.053 kg

COLOURS

Colour:

Black, similar to RAL 9005

CERTIFICATES

conforming to the standards:

IEC 61439-2

SALES DATA

Product number: 2000311
EAN: 4012591653110
Pack unit: 1
Customs tariff number: 85371098
ETIM class: DYNAMIC: EC002620 - Components for installation (enclosure/
cabinet)
ETIM-9.0: EC002620 - Components for installation (enclosure/
cabinet)
ETIM-8.0: EC002620 - Components for installation (enclosure/
cabinet)
ETIM-7.0: EC002620 - Components for installation (enclosure/
cabinet)
ETIM-6.0: EC002620 - Components for installation (enclosure/
cabinet)
ETIM-5.0: EC002620 - Components for installation (enclosure/
cabinet)
ETIM-4.0: EC002620 - Components for installation (enclosure/
cabinet)

NOTE

Note on the product:

- Set, consisting of 1 seal, 4 wedge connectors, 1 clamp

TENDER TEXT

Insulation-enclosed power distribution board as power switchgear and controlgear assembly (PSC) in accordance with IEC 61439-2 for wall mounting. The enclosures must be suitable for outdoor installation - harsh environment and/or outdoor installation - the climatic effects on the equipment must be considered. Bottom parts and lids of the boxes made from impact-resistant polycarbonate, halogen and silicone-free, colour RAL 7035, transparent lid with quick action fasteners for tool operation. Burning behaviour according to IEC 60695-2-11 glow wire test + 960°C. Maximum water absorption 10 mg in accordance with DIN 53473. Protective measure: totally insulated (protection class II), Make: HENSEL Mi Power distribution board., Wall gasket Mi WD 2, with fastening elements, for Mi box walls 150 or 300 mm

DRAWINGS

