



Mi ZE 62

- Strain relief

CONNECTION DATA

MECHANICAL PROPERTIES

Delivered accessories:

Fastening material

AMBIENT CONDITIONS

Application area:

Indoor installation

Maximum ambient temperature 24 h:

35 °C

Ambient temperature:

-5 °C up to +40 °C

Relative humidity:

≤ 50 % at 40 °C, ≤ 100 % at 25 °C

MATERIAL PROPERTIES

Material:

Steel

DIMENSIONS

Width:

284 mm

Net weight:

0.612 kg

CERTIFICATES

conforming to the standards:

IEC 61439-2

SALES DATA

Product number: 2000354
EAN: 4012591653547
Pack unit: 1
Customs tariff number: 85371098
ETIM class: DYNAMIC: EC000322 - Cable guide for enclosures/cabinets
ETIM-9.0: EC000322 - Cable guide for enclosures/cabinets
ETIM-8.0: EC000322 - Cable guide for enclosures/cabinets
ETIM-7.0: EC000322 - Cable guide for enclosures/cabinets
ETIM-6.0: EC000322 - Cable guide for enclosures/cabinets
ETIM-5.0: EC000322 - Cable guide for enclosures/cabinets
ETIM-4.0: EC000322 - Cable guide for enclosures/cabinets

NOTE

Note on the product:

- for 2 cables with max. 60 mm external diameter
- To be used only in connection with Mi FP 82

TENDER TEXT

Insulation-enclosed power distribution board as power switchgear and controlgear assembly (PSC) in accordance with IEC 61439-2 for wall mounting. The enclosures must be suitable for outdoor installation - harsh environment and/or outdoor installation - the climatic effects on the equipment must be considered. Bottom parts and lids of the boxes made from impact-resistant polycarbonate, halogen and silicone-free, colour RAL 7035, transparent lid with quick action fasteners for tool operation. Burning behaviour according to IEC 60695-2-11 glow wire test + 960°C. Maximum water absorption 10 mg in accordance with DIN 53473. Protective measure: totally insulated (protection class II), Make: HENSEL Mi Power distribution board., Cable strain relief Mi ZE 62, 2 x max. Ø 60 mm, can be used in connection with flange Mi FP 82