



DK 1600 G

IP
66

16 mm²

- without terminals
- Dimensions H x W x D: 155 x 210 x 92 mm
- with metric knockouts

ELECTRICAL PROPERTIES

Rated insulation voltage:

U_i = 1000 V

CONNECTION DATA

CABLE ENTRIES

Cable entries:

Number of cable entries	Type of cable entry	Size of the metric knockouts	Location of cable entry
10	metric knockouts	M25, M32, M40	wall
2	metric knockouts	M32	bottom

MECHANICAL PROPERTIES

Type of lid fastening:

Quick locking: Opening and closing by quarter turn, locked position well visible (open - locked)

Delivered accessories:

External brackets, sealing plug

IP degree of protection:

IP66

IP degree of protection of the included Grommets 3x ESM 40:

IP55, sealing range

Impact strength:	IK07
Sealable without accessories:	Yes

AMBIENT CONDITIONS

Application area:	Indoor installation
Maximum ambient temperature 24 h:	35 °C
Ambient temperature:	-25 °C up to +40 °C
Relative humidity:	≤ 50 % at 40 °C, ≤ 100 % at 25 °C

MATERIAL PROPERTIES

Material:	Polycarbonate
Glow wire test according to IEC 60695-2-11:	750 °C
UL 94:	V-2
Temperature resistance:	-25 °C up to +80 °C
Halogen-free:	Yes
Silicone-free:	Yes

DIMENSIONS

Height:	155 mm
Width:	210 mm
Depth:	92 mm
Net weight:	0.444 kg
Mounting height:	120 mm
Mounting width:	175 mm
Mounting depth:	76 mm

COLOURS

Colour:	Grey, similar to RAL 7035
---------	---------------------------

CERTIFICATES

conforming to the standards:	DIN EN 60670-1/-22, IEC 60670-1/-22
------------------------------	-------------------------------------

Certificates:

Type of certificate	Certificate number
VDE	40049684

SALES DATA

Product number:	62000012
EAN:	4012591125044
Pack unit:	2
Customs tariff number:	85369010
ETIM class:	DYNAMIC: EC002600 - Box/housing for surface mounting on the wall/ceiling ETIM-8.0: EC002600 - Box/housing for surface mounting on the wall/ceiling ETIM-7.0: EC002600 - Box/housing for surface mounting on the wall/ceiling ETIM-6.0: EC002600 - Box/housing for surface mounting on the wall/ceiling ETIM-5.0: EC002600 - Box/housing for surface mounting on the wall/ceiling ETIM-4.0: EC002600 - Box/housing for surface mounting on the wall/ceiling

NOTE

When using the sealing plugs supplied, the specified protection class is not changed.

TENDER TEXT

Nominal cross-section: 16 mm², dimensions HxWxD 155 x 210 x 92 mm, Cable junction boxes in accordance with IEC 60670-22 with metric knockouts. Suitable for indoor and protected outdoor installation in accordance with DIN VDE 0100, part 737. For ambient temperatures of maximum value +40 °C and minimum value -25 °C, with relative humidity of 50 % at +40 °C or 100 % at +25 °C. Material temperature resistance from -25 °C to +70 °C, burning behaviour according to IEC 60695-2-11 - glow wire test 750°C, UL Subject 94 V-2. Degree of protection in accordance with IEC 60529: IP 66 with AKM cable glands. Rated insulation voltage: 1000 V. Material: thermoplastics, halogen- and silicone-free. Colour: grey, RAL 7035. Lid fastening with quick fasteners, sealable without accessories. Plug-in external brackets for wall mounting included. Make: HENSEL ENYCASE DK.

DRAWINGS

