



## KF 1600 B



- without terminals
- Dimensions H x W x D: 155 x 210 x 92 mm
- with metric knockouts

## ELECTRICAL PROPERTIES

Rated insulation voltage:  $U_i = 1000 \text{ V}$

## CONNECTION DATA

### CABLE ENTRIES

Cable entries:

Number of cable entries	Type of cable entry	Size of the metric knockouts	Location of cable entry
10	metric knockouts	M25, M32, M40	wall
2	metric knockouts	M32	bottom

## MECHANICAL PROPERTIES

Type of lid fastening:

Quick locking: Opening and closing by quarter turn, locked position well visible (open - locked)

Delivered accessories:	External brackets, sealing plug, external brackets, retaining strap, sealing plug
IP degree of protection:	IP66, IP67, IP69
	IP67: Temporary submersion up to 1 m / 30 min
	IP69: Water pressure max. 100 bar, water temperature max. 80 °C, distance $\geq$ 0.15 m

Impact strength:	IK09
Sealable without accessories:	Yes

## AMBIENT CONDITIONS

To reduce the formation and accumulation of condensed water see technical information "Formation of condensed water and retaliatory actions"

Application area:	Outdoor installation
Maximum ambient temperature 24 h:	55 °C
Ambient temperature:	-25 °C up to +70 °C
Relative humidity:	$\leq$ 50 % at 40 °C, $\leq$ 100 % at 25 °C

## MATERIAL PROPERTIES

Material:	Polycarbonate
Glow wire test according to IEC 60695-2-11:	960 °C
UL 94:	V-0
Temperature resistance:	-25 °C up to +100 °C
Halogen-free:	Yes
Silicone-free:	Yes
Weatherproof:	Yes (resistant to UV exposure due to solar radiation, ice and sea water, corrosion, temperature resistant, impact-resistant)

## DIMENSIONS

Height:	155 mm
Width:	210 mm
Depth:	92 mm
Net weight:	0.404 kg
Mounting height:	120 mm
Mounting width:	175 mm
Mounting depth:	76 mm

## COLOURS

Colour:	Black, similar to RAL 9011
---------	----------------------------

## CERTIFICATES

conforming to the standards: DIN EN 60670-1/-22, IEC 60670-1/-22

Certificates:

Type of certificate	Certificate number
VDE	40041432
DNV GL	TAE00000EE

## SALES DATA

Product number:	62000064
EAN:	4012591121923
Pack unit:	2
Customs tariff number:	85369010
ETIM class:	DYNAMIC: EC002600 - Box/housing for surface mounting on the wall/ceiling ETIM-8.0: EC002600 - Box/housing for surface mounting on the wall/ceiling ETIM-7.0: EC002600 - Box/housing for surface mounting on the wall/ceiling ETIM-6.0: EC002600 - Box/housing for surface mounting on the wall/ceiling ETIM-5.0: EC002600 - Box/housing for surface mounting on the wall/ceiling ETIM-4.0: EC002600 - Box/housing for surface mounting on the wall/ceiling

## NOTE

When using the sealing plugs supplied, the specified protection class is not changed.

## TENDER TEXT

Nominal cross-section: 16 mm<sup>2</sup>, dimensions HxWxD 155 x 210 x 92 mm, Cable junction boxes in accordance with IEC 60670-22, with metric knockouts. Suitable for indoor and unprotected outdoor installation in accordance with DIN VDE 0100, part 737. For ambient temperatures maximum value +70 °C and minimum value -25 °C, with relative humidity of 50 % at +40 °C or 100 % at +25 °C. Material temperature resistance from -25 °C to +90 °C, burning behaviour according to IEC 60695-2-11 - glow wire test 960 °C, UL Subject 94 V-0. Degree of protection in accordance with IEC 60529: IP 66 / IP 67 / IP 69 with ASS cable glands. Degree of protection IP 69 up to 100 bar water pressure at a maximum of +80 °C water temperature and 0.15 m minimum distance, without cleaning additives. Material: PC thermoplastics, weatherproof, halogen- and silicone-free. Colour: black RAL 9011. Lid fastening with quick fasteners, sealable without accessories. Plug-in external brackets for wall mounting included. Make: HENSEL KF.

## DRAWINGS

